



MeiG Smart SLM828 Module

LTE-A Cat.6 Mini PCIe Packaging Module

MeiG Smart SLM828 is LTE Advanced module optimized specially for M2M and IoT applications.

Adopting the 3GPP Rel.12 LTE technology and CA technology, it delivers maximum 300Mbps downlink and 50Mbit/s uplink peak data rates.

SLM828 LTE-A module contains two variants: SLM828-EU and SLM828-NA.

SLM828 module adopts MIMO technology, a cutting edge antenna technology capable of transmit multiple data streams from multiple transmitters to multiple receivers. SLM828 also combines Highsensitivity GNSS receiver for positioning.

A rich set of protocols (TCP/FTP/HTTP) and multiple OS compatibility extend the applicability of the module to a wide range of M2M applications

Key Technologies:

- ▣ SLM828 has a maximum downlink rate of 300Mbps and a maximum upstream rate of 50Mbps.
- ▣ Support DL 2CA, 3CA
- ▣ Qualcomm® IZat™ Gen 8C engine, Support GPS/ GLONASS/BeiDou
- ▣ Support Voice Codec (HR/FR/EFR/AMR/AMR-WB), Support SRLTE/CSFB/VOLTE (optional)
- ▣ USB2.0/USB3.0 High Speed Interface
- ▣ TCP/IP Embedded Protocol Stacks



LTE-A



PCM



ADC



MIMO



Wi-Fi



GNSS



UART



VoLTE

MeiG Smart SLM828 Module

LTE-A Cat.6 Mini PCIe Packaging Module

MEIG

General Features:

- ❑ Package: MiniPCIe package (52pin)
- ❑ Size: 51.0×30.0×4.5mm
- ❑ Weight: < 10g
- ❑ Supply Voltage: 3.1V~4.2V, Typ 3.3V
- ❑ Sleep Power: < 5mA

Data Features:

- ❑ LTE (Cat.6):Max 300Mbps(DL)/50Mbps(UL)
- ❑ DC-HSPA+:Max 42Mbps(DL)/5.76Mbps(UL)
- ❑ WCDMA: Max 384kbps(DL)/384kbps(UL)

Transmit Power:

- ❑ WCDMA/HSPA 23+1/-3dBm, LTE 23±2.7dBm

Protocols:

- ❑ TCP*/UDP*/SSL*/HTTP(S)*/FTP*/PPP/PING/DTMF*/QMI

Drivers & Tools:

- ❑ Drivers: Windows XP,Windows Vista,Windows 7, Windows 8,Windows 8.1,Windows 10, Linux, Android
- ❑ Tools: One Click update tool, Gobinet Dial Tool
- ❑ *FOTA upgrade

Working Environment:

- ❑ Restrict Working Temperature: -40°C to 85°C
- ❑ Storage Temperature: -45°C to 90°C
- ❑ Humidity: 5%~95%

Band Description of SLM828:

PID	Frequencies	CA	GNSS
SLM828-EU	LTE-FDD: B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD: B38/B40/B41 WCDMA: B1/B3/B5/B8	Intra contiguous:CA_1C,CA_3C,CA_5B,CA_7B,CA_7C,CA_8B,CA_38C,CA_40C,CA_41C; Intra Non-contiguous: CA_1A-1A,CA_3A-3A,CA_5A-5A,CA_7A-7A,CA_40A-40A,CA_41A-41A; Inter band CA: CA_1A-3A,CA_1A-5A,CA_1A-7A,CA_1A-8A,CA_1A-20A,CA_1A-28A,CA_1A-38A,CA_1A-40A,CA_1A-41A, CA_3A-5A,CA_3A-7A,CA_3A-8A,CA_3A-20A,CA_3A-28A,CA_3A-38A,CA_3A-40A,CA_3A-41A, CA_5A-7A,CA_5A-38A,CA_5A-40A,CA_5A-41A, CA_7A-8A,CA_7A-20A,CA_7A-28A,CA_7A-32A, CA_8A-32A,CA_8A-38A,CA_8A-40A,CA_8A-41A,CA_20A-32A, CA_20A-38A,CA_20A-40A, CA_28A-32A,CA_28A-38A,CA_28A-40A,CA_28A-41A	Option
SLM828-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/14/17/ B25/B26/B29/B30/B66/B71 WCDMA: B2/B4/B5	Intra contiguous:CA_2C,CA_5B,CA_7B,CA_7C,CA_12B; Intra Non-contiguous:CA_2A-2A,CA_4A-4A,CA_5A-5A,CA_7A-7A,CA_12A-12A,CA_25A-25A,CA_66A-66A; Inter band CA: CA_2A-4A,CA_2A-5A,CA_2A-7A,CA_2A-12A,CA_2A-13A,CA_2A-14A,CA_2A-29A,CA_2A-30A,CA_2A-66A, CA_2A-71A, CA_4A-5A,CA_4A-7A,CA_4A-12A,CA_4A-13A,CA_4A-29A,CA_4A-71A, CA_5A-7A,CA_5A-25A,CA_5A-30A,CA_5A-66A, CA_7A-12A,CA_7A-20A,CA_7A-28A, CA_12A-25A,CA_12A-30A,CA_12A-66A, CA_13A-66A, CA_14A-30A,CA_14A-66A, CA_25A-26A, CA_29A-30A,CA_29A-66A, CA_66A-71A	Option



Interfaces:

- ❑ USB 2.0/USB 3.0
- ❑ UART×3
- ❑ SIM card Interface(1.8 / 3.0V)
- ❑ Antenna Interface: Main/Diversity/GNSS (Optional)
- ❑ I2C×1
- ❑ SDIO×1
- ❑ Power On/Off,Reset
- ❑ ADC×2
- ❑ SPI×1
- ❑ PCM×1
- ❑ PCIe×1
- ❑ GPIOs

Authentication information:

- ❑ CE/FCC/PTCRB

MeiG Smart Technology Co.,Ltd

A Global Leading Supplier of Cellular Modules and Solutions

Add : 32/F, Building B, Shenzhen International Innovation Center,
No. 1006 Shennan Avenue, Futian District, Shenzhen, China
Tel : +86-755-83218588 Fax : +86-755-83219788
E-mail : ir@meigsmart.com Web : www.meigsmart.com



MeiG Official Wechat QR Code